

DIM19S



LED- Sunlight Readable In-outdoor LCD Monitor

This product features the latest in LCD technology with 1,500nit LED backlights rated at 100,000 hours life.

This product feature LED Backlights (Direct sunlight readable), optically bonded anti-reflective glass, perfect 1000:1 dimming, DVI, VGA, S-Video, Composite, HDMI and Mil Spec. OSD controls.

Features

- 19.0" TFT LCD
- 1,280 X 1,024 Resolution(SXGA)
- 12VDC 3.0A Option: 24V or 28V DC, AC 110/220V
- Applications: In-Outdoor, Marine, Air craft, Vehicles.

Specifications

LCD Type	TFT Active Matrix LCD (16.7 Million colors)
Display Size	19.0"
Resolution	1,280 x 1,024(SXGA)
Contrast Ratio	1,000:1
Brightness	LED Backlight Type- 1,500 nit(min.)
Panel Surface	Anti-Glare Coating with Tempered Glass
Inputs	DVI,VGA, Composite, S-Video, HDMI(With PIP/POP)
Mounting Options	VESA / Flush/U-Bracket mounted
View Angle	170(H) 170 (V)
Response Time	3m/sec
Light Source	Light Emitting Diodes
Input Voltage	DC12V @ 2.5A (Option: AC 110/220V)
Power Consumption	34W
Out-dimensions	14.96"(W)x17.51"(H)x2.23"(D), 380(W)x445(H)x56.8(D)mm
Operating Range	-10C ~ 60C
Cases Color	Black ,Dark Gray
IP Rating	Front Side:IP65, Rear Side:IP32
Warranty	2 yrs
Dimming Range	1000:1 (dimming control to dark to full bright)
Weight	13.67 LBS(6.2Kg)
Touch Screen	Resistive, Projective Capacitive

Dizen Systems.

9720. Orizaba Ave, Downey, CA90240. USA

E-mail:sales@dizensystems.com

Web-Site: www.dizensystems.com

DIZEN SYSTEMS